CLAIMS

What is claimed is:

5

10.20 II and all fall fall

L

- 1. A method for routing data packets in a network, comprising grouping routing-table entries into numbered clusters for lookup of a routing-table entry based on cluster number and destination address.
- 2. A method as recited in claim 1, further comprising assigning a cluster number to a data packet.
- 3. A method as recited in claim 2, further comprising routing said data packet based on a routing-table entry selected from a group of routing-table entries based on said cluster number and a destination address associated with said data packet.
- 4. A method as recited in claim 3, further comprising replacing said cluster number of said data packet with a new cluster number when said packet is routed.
- 5. A method as recited in claim 2, further comprising matching the cluster number associated with said data packet to a corresponding cluster number associated with said routing-table entries.

20

6. A method as recited in claim 5, further comprising searching routing-table entries associated with said cluster number using a destination address associated with

UC00-385-2

- 7. A method as recited in claim 6, further comprising routing said data packet using a routing-table entry corresponding to said destination address.
- 8. A method as recited in claim 7, further comprising replacing said cluster number of said data packet with a new cluster number when said packet is routed.
- 9. A method as recited in claim 1, further comprising assigning a Cluster Number (Incoming) and a Cluster Number (Outgoing) to each routing table entry.
- 10. A method as recited in claim 9, further comprising assigning a Cluster Number (Incoming) to said data packet.
- 11. A method as recited in claim 10, further comprising routing said data packet based on a routing-table entry selected from a group of routing-table entries corresponding based on said Cluster Number (Incoming) and a destination address associated with said data packet.
- 12. A method as recited in claim 11, further comprising replacing said Cluster Number (Incoming) of said data packet with the Cluster Number (Outgoing) associated with said selected routing-table entry when said data packet is routed.

5

13.

14. A method as recited in claim 13, further comprising searching routing-table entries associated with said Cluster Number (Incoming) using a destination address associated with said data packet as an index.

Number (Incoming) associated with said data packet to a corresponding Cluster

Number (Incoming) associated with said routing-table entries.

A method as recited in claim 9, further comprising matching the Cluster

- 15. A method as recited in claim 14, further comprising routing said data packet using a routing-table entry corresponding to said destination address.
- 16. A method as recited in claim 15, further comprising replacing said Cluster Number (Incoming) of said data packet with the Cluster Number (Outgoing) associated with said corresponding routing-table entry when said data packet is routed.
- 17. A method for routing data packets in a network, comprising:
 grouping routing-table entries into numbered clusters for lookup of a routing-table
 entry based on cluster number and destination address; and

routing a data packet based on a routing-table entry selected from a group of routing-table entries based on a cluster number and a destination address associated with said data packet.

in in

20

Press II gir.

1Q1

UC00-385-2 51 EL484718580US

- 19. A method as recited in claim 17, further comprising matching the cluster number associated with said data packet to a corresponding cluster number associated with said routing-table entries.
 - 20. A method as recited in claim 19, further comprising searching routing-table entries associated with said cluster number using a destination address associated with said data packet as an index.
 - 21. A method as recited in claim 20, further comprising routing said data packet using a routing-table entry corresponding to said destination address.
 - 22. A method as recited in claim 21, further comprising replacing said cluster number of said data packet with a new cluster number when said packet is routed.
 - 23. A method as recited in claim 17, further comprising assigning a Cluster Number (Incoming) and a Cluster Number (Outgoing) to each routing table entry.
 - 24. A method as recited in claim 23, further comprising assigning a Cluster Number (Incoming) to said data packet.

20

5

UC00-385-2

25. A method as recited in claim 24, further comprising routing said data packet based on a routing-table entry selected from a group of routing-table entries corresponding based on said Cluster Number (Incoming) and a destination address associated with said data packet.

5

1**0**0

Harm H. H. Harm

Fub

Hrre drug press 1

15.4 []

- 26. A method as recited in claim 25, further comprising replacing said Cluster Number (Incoming) of said data packet with the Cluster Number (Outgoing) associated with said selected routing-table entry when said data packet is routed.
- 27. A method as recited in claim 23, further comprising matching the Cluster Number (Incoming) associated with said data packet to a corresponding Cluster Number (Incoming) associated with said routing-table entries.
- 28. A method as recited in claim 27, further comprising searching routing-table entries associated with said Cluster Number (Incoming) using a destination address associated with said data packet as an index.
- 29. A method as recited in claim 28, further comprising routing said data
 20 packet using a routing-table entry corresponding to said destination address.

UC00-385-2 53 EL484718580US

31. A method for routing data packets in a network, comprising:

grouping routing-table entries into numbered clusters for lookup of a routing-table entry based on cluster number and destination address;

matching a cluster number associated with a data packet to a corresponding cluster number associated with said routing-table entries; and

routing said data packet based on a routing-table entry selected from a group of routing-table entries based on the cluster number and the destination address associated with said data packet.

- 32. A method as recited in claim 31, further comprising replacing said cluster number of said data packet with a new cluster number when said packet is routed.
- 33. A method as recited in claim 31, further comprising searching routing-table entries associated with said cluster number using a destination address associated with said data packet as an index.

20

5

(1) 10()

١.

10 mm 10 mm 12 mm

e 6-3

15±

UC00-385-2 54 EL484718580US

5

34. A method for routing data packets in a network, comprising: grouping routing-table entries into clusters;

assigning a Cluster Number (Incoming) and a Cluster Number (Outgoing) to each routing table entry;

assigning a Cluster Number (Incoming) to a data packet;

matching the Cluster Number (Incoming) associated with said data packet to a corresponding Cluster Number (Incoming) associated with said routing-table entries;

searching routing-table entries associated with said Cluster Number (Incoming) of said data packet using a destination address associated with said data packet as an index; and

routing said data packet based on a routing-table entry corresponding to the destination address associated with said data packet.

- 35. A method as recited in claim 34, further comprising replacing said Cluster Number (Incoming) of said data packet with the Cluster Number (Outgoing) associated with said selected routing-table entry when said data packet is routed.
 - 36. A method for routing data packets in a network, comprising: grouping routing-table entries into clusters;
- assigning a Cluster Number (Incoming) and a Cluster Number (Outgoing) to each routing table entry;

assigning a Cluster Number (Incoming) to a data packet;

UC00-385-2 55 EL484718580US

matching the Cluster Number (Incoming) associated with said data packet to a corresponding Cluster Number (Incoming) associated with said routing-table entries;

searching routing-table entries associated with said Cluster Number (Incoming) of said data packet using a destination address associated with said data packet as an index;

routing said data packet based on a routing-table entry corresponding to the destination address associated with said data packet; and

replacing said Cluster Number (Incoming) of said data packet with the Cluster Number (Outgoing) associated with said selected routing-table entry when said data packet is routed.